

BALISTICA FORENSE

Osservazioni critiche su certo uso improprio che mi è capitato di vedere in alcuni elaborati di consulenti balistici italiani dell'articolo pubblicato nella rivista AFTE Journal, 1999, 31 (2), 117-122 di Frederic A. Tulleners e James S. Hamiel, intitolato "Sub Class Characteristics of Sequentially Rilled 38 Special S&W Revolver Barrels"

Biagio Manetto

Esperto Balistico
già Ispettore Capo della Polizia di Stato
con 25 anni di esperienza maturata presso
G.R.P.S. di Palermo, prima come addetto
e poi come responsabile della
Sezione Balistica

Docente del Master in
Applicazioni Scientifiche e
Tecnologiche nelle Indagini Forensi
2010-2015
Università di Palermo - Facoltà di Scienze

Tel.: 0921.309.000
Cell.: 349.404.4613

Internet: www.manetto.it
e-mail: biagio@manetto.it

Via Palermo snc - 98072 Caronia (ME)

Premessa

Più volte mi è capitato di leggere relazioni balistiche o di confrontarmi in dibattimento con consulenti i quali, a sostegno delle loro tesi, richiamano il contenuto dell'interessante articolo di Frederic A. Tulleners e James S. Hamiel, intitolato "Sub Class Characteristics of Sequentially Rilled 38 Special S&W Revolver Barrels".

Ovviamente non ci trovo nulla di male che vengano richiamati lavori scientifici per sostenere un proprio percorso tecnico-balistico; trovo, però, puerile e del tutto privo di coerenza scientifica richiamare quest'articolo per controbattere lavori di balistica comparativa ampiamente corroborati di documentazione fotografica che dimostra l'esistenza di tracce coincidenti sia sui cavi che sui pieni dei proiettili comparati.

A beneficio dei non esperti, al fine di comprendere meglio quanto esposto, ricordo che le impronte di subclasse sono tutte quelle tracce che si possono trovare sui bossoli e sui proiettili in quanto lasciate dalle macchine utilizzate nella fabbricazione delle armi e delle munizioni.

In sintesi il lavoro pubblicato dai due ricercatori americani (in allegato in calce alla presente nota)

Frederic A. Tulleners e James S. Hamiel, effettuano la ricerca nel 1979 presso la fabbrica Smith & Wesson. Si fanno dare dieci canne fabbricate in successione, le numerano e le montano di volta in volta su un revolver calibro 38 Special. Ottengono dei proiettili test, li comparano e trovano sugli interspazi dei solchi (pieni sul proiettile) delle microstrie che sono perfettamente coincidenti, come si può constatare nella seguente figura (una delle cinque foto pubblicate nell'articolo) dove viene comparato un proiettile test proveniente dalla canna 6 (a sinistra) ed un proiettile test proveniente dalla canna 8 (a destra).

BALISTICA FORENSE - Osservazioni critiche su certo uso improprio che mi è capitato di vedere in alcuni elaborati di consulenti balistici italiani dell'articolo pubblicato nella rivista AFTE Journal, 1999, 31 (2), 117-122 di Frederic A. Tulleners e James S. Hamiel, intitolato "Sub Class Characteristics of Sequentially Rilled 38 Special S&W Revolver Barrels"





Fig. 4 Groove impressions barrel 6 T-2 (G-3) to barrel 8 T-1 (G-3)

I due ricercatori precisano che sui Land (cavi) della rigatura non riscontrano la presenza di impronte di subclasse (v. figura seguente).


This article illustrates subclass characteristics found in groove impressions on lead bullets that were fired from 10 sequentially manufactured 38 Special, Smith & Wesson revolver barrels. These subclass characteristics were present on some, but not all of the ten sequential barrels and in some but not all of the groove impressions. These barrels were rifled using the step cutting broach-manufacturing process. **These subclass characteristics were not found on the land impressions of the fired lead bullets or on the land or groove impressions of the copper-jacketed bullets.**




In questa figura riporto quanto scritto da Frederic A. Tulleners e James S. Hamiel. In blu i pieni dei proiettili (groove) dove viene riscontrata l'identità delle impronte di subclasse.

Perché sui land (cavi) non si trovano impronte di subclasse ?


Provo a dare una spiegazione tecnica, esaminando nel dettaglio il processo che porta alla fabbricazione delle canne dove il foro viene realizzato per broccatura (come quelle delle Smith & Wesson sulle quali si è condotto l'esperimento).



Rigatura ottenuta per ogivazione o broccatura



SI PARTE CON UNA BARRA DI ACCIAIO...




... CHE VIENE FORATA PER POTERVI INTRODURRE LA BROCCIA CHE CONSENTE DI OTTENERE LA RIGATURA


La barra pre-forata viene lavorata con la broccia.



PER BROCCIATURA LA RIGATURA VIENE OTTENUTA PER INTAGLIO DEL METALLO ED ASPORTAZIONE DEI TRUCIOLI E ...




... AL TERMINE DELL'OPERAZIONE, L'ANIMA DELLA CANNA PRESENTA LE CARATTERISTICHE NERVATURA CHE SERVONO A CONFERIRE AL PROIETTILE UN MOTO ROTATORIO INTORNO AL PROPRIO ASSE E STABILIZZARLO IN TRAIETTORIA.




Dopo la brocciatura l'anima della canna viene spazzolata e lucidata. Tale intervento è più efficace sulla faccia delle nervature ...

... mentre negli interspazi delle nervature non riesce ad asportare efficacemente le tracce lasciate dalla broccia.

La canna finita viene montata sull'arma e messa in commercio.




Il proiettile sparato, attraversando la canna, si trafilà e ...



... copia in negativo le tracce che caratterizzano gli interspazi, in azzurro, che sul proiettile diventano *pieni* (*groove in inglese*) e le nervature, in rosso, che sul proiettile diventano *cavi* (*land in inglese*).

Ecco il motivo per cui i due ricercatori non trovano identità di subclasse sui cavi (land) dei proiettili!

This article illustrates subclass characteristics found in groove impressions on lead bullets that were fired from 10 sequentially manufactured 38 Special, Smith & Wesson revolver barrels. These subclass characteristics were present on some, but not all of the ten sequential barrels and in some but not all of the groove impressions. These barrels were rifled using the step cutting broach-manufacturing process. These subclass characteristics were not found on the land impressions of the fired lead bullets or on the land or groove impressions of the copper-jacketed bullets.



Conclusioni

Se effettuiamo la comparazione al fine di stabilire che due proiettili provengono dalla medesima arma è indispensabile comparare il patrimonio di microstrie che troviamo nei cavi (lands in inglese), dove siamo certi che il processo di finitura della canna ha portato via tutti quei segni di lavorazione lasciate dalla broccia. Si può estendere la comparazione anche ai pieni (groove) ma non basarla, esclusivamente, sulle tracce trovate negli interspazi.

Trovo corretto richiamare il lavoro di Frederic A. Tulleners e James S. Hamiel per far emergere la lacunosità di comparazioni basate esclusivamente sui pieni dei proiettili (interspazi), ma eviterei di farlo se sono in presenza di una sequenza fotografica che dimostra l'identità di microstrie presenti su cavi di rigatura che, si ricorda, vengono lasciate dalle nervature della canna.

Durante la fase di accertamento è indispensabile distinguere se le tracce che si stanno comparando sono da attribuirsi a quell'arma in quanto peculiari dell'esemplare in esame o sono impronte di subclasse e, giustamente i due ricercatori precisano che non hanno riscontrato sui Land (cavi) dei proiettili la presenza di impronte di subclasse.

Caronia, 6 settembre 2015

Biagio Manetto

Sub Class Characteristics of Sequentially Rifled 38 Special S&W Revolver Barrels

Frederic A. Tulleners^{*} and James S. Hamiel^{**}
California Criminalistics Institute (CCI)
4949 Broadway Room A104
Sacramento, CA 95820

Abstract:

This article illustrates subclass characteristics found in groove impressions on lead bullets that were fired from 10 sequentially manufactured 38 Special, Smith & Wesson revolver barrels. These subclass characteristics were present on some, but not all of the ten sequential barrels and in some but not all of the groove impressions. These barrels were rifled using the step cutting broach-manufacturing process. These subclass characteristics were not found on the land impressions of the fired lead bullets or on the land or groove impressions of the copper-jacketed bullets

Background:

Test bullets were fired¹ from 10 sequentially rifled Smith & Wesson (S&W) 38 Spl. Revolver barrels. The barrels were obtained from R.G. Jinks of Smith and Wesson in 1979 for use in exercises in Toolmark Comparison Criteria classes offered by the Bureau of Forensic Service and subsequently by the CCI. The following rifling operations² were completed in sequential order with barrel #1 being the first one through each operation, and barrel #10 being the last.

1. Barrels were micro honed to improve bore finish (assumed to be performed before the rifling process).
2. They were rifled (i.e., multi step, single pass broach).
3. They were button burnished.
4. Forcing Cone Cut

Each of the 10 sequentially rifled barrels was individually mounted in the same S&W revolver frame, which was then used to fire five (5) sets, each consisting of three .38 SPL. Lead bullets, followed by three Jacketed Soft Point (JSP) test bullets in sequential order for each barrel, using water recovery. The barrels were not cleaned prior to, or during, the firing of each test set. No casts were made of the rifling in these test barrels prior to or after the tests were fired. All barrels were returned to S&W after firing each set. Attempts to have these barrels returned for evaluation after the subclass phenomena was discovered were unsuccessful.

^{*} Frederic A. Tulleners, Program Manager, CCI

^{**} James Hamiel, Research Intern, CCI

Each test set from each barrel #1 to #10 consists of three (3) lead tests, followed by three (3) JSP tests numbered sequentially in the order in which they were fired. Each barrel was fired a total of 30 times and the test firings alternated between sets of three lead bullets followed by sets of three copper jacketed bullets. The bullets were labeled sequentially from T1 up to T30. Thus five sets were fired (a set consisting of three lead bullets followed by three copper-jacketed bullets).

Discussion:

Subclass characteristics are defined³ as discernable surface features of an object which are more restrictive than "Class Characteristics" in that they are produced incidental to manufacture, 2) Are significant in that they relate to a smaller group source and 3) Can arise from a source which changes over time. It is critical for the examiner to have a thorough understanding of the influence of subclass characteristics so that they can be recognized when they are present so that striae produced by them do not form the basis for identification.

The photographs in Figure 1 to 5 illustrate the correspondence in the subclass features in the groove impressions of the lead bullets. These are illustrated with the use a Reichert comparison microscope with an approximate magnification of 30X. These five photographs depict the best correspondence of the subclass characteristics found on these bullets. If these striae were not caused by subclass features of the rifling tool, the extent of this agreement would be sufficient for an identification. There are a few other areas showing correspondence but not to the extent exhibited in figures 1-5. In particular, the groove impressions of bullets # 4, #5 and #6 appear to best illustrate the agreement of the subclass characteristics. Overall it appears that barrel 6 test #2, groove #3, provides the




Fig. 1 Groove impressions barrel 6 T-1 (G-3) to barrel 5 T1 (G5)

best correspondence to the other grooves. The land impressions of these lead bullets did not illustrate any subclass characteristic features.



Fig.2 Groove impressions barrel 4 T-2 (G-4) to barrel 5 T-1 (G-5)




Fig. 3 Groove impressions barrel 6 T-2 (G-3) to barrel 7 T-1 (G-1)




Fig. 4 Groove impressions barrel 6 T-2 (G-3) to barrel 8 T-1 (G-3)




Fig. 5 Groove impressions barrel 7 T-1 (G-1) to barrel 8 T-1 (G-3)

Biasotti⁴ previously illustrated a series of PLASTISOL⁵ replicas of barrels manufactured by the step cutting broach process. From a comparison of PLASTISOL casts taken two inches apart, it is quite evident that there are substantial changes in the barrel groove striae to such an extent that one would not expect any reproducibility from consecutive barrels. However, subclass characteristics can occur if the tool is damaged and carries with it some major imperfections. Lomoro⁶ illustrates a series of subclass characteristics from Titan revolvers caused by a similar manufacturing mechanism. These subclass characteristics were likewise found only in the groove impressions and not in the land impressions of the bullets. This subclass carry over noted by Lomoro consisted of much coarser striae than observed on the S&W barrels.

The evaluation of these S&W subclass characteristics was originally performed by Al Biasotti⁷ who stated:

"The subclass characteristics are noted in a limited number of groove impressions on lead tests from the 10 sequentially rifled S&W, 38 Spl., revolver barrels. Without having the barrels, or casts to examine, the reason why these remarkable subclass characteristics occurred cannot be fully explained. However, based on the limited extent of the similarities noted by my personal observations, it can be concluded that the similarities noted represent an extremely rare event that would not be expected to be encountered in actual case situations". While this statement may be true for the manufacture of revolvers, the current practice of having a long rifled barrel sectioned into multiple short pistol barrels may increase the chance for this type of subclass event.

Conclusion:

In a letter to CCI students, Biasotti's⁸ conclusions were stated as:

"The most important lessons to be learned from all of the striated toolmark-bullet comparison exercises are:

1. That the chance occurrence of more than 3 or 4 consecutively corresponding striae is an extremely rare event, rising exponentially with increasing combinations of 2 or more consecutively corresponding striae. Therefore, the concept of consecutive striae is the most effective criteria for determining common origin of toolmarks.
2. That the occurrence of subclass characteristics in rifled firearms barrels is a rare event that can be easily determined by the direct inspection of the rifling or a barrel cast; and where the barrel or barrel cast is not available, by applying a more consecutive criteria in determining common origin."

This expression of numerical criteria for identification has been refined recently and appears in a chapter by Biasotti and Murdock⁹

Summary:

Since 1991 the bullets have been used as part of a series of exercises in the annual "Toolmark Criteria for Identification" class held at the CCI. During these exercises numerous experienced, and some inexperienced, firearm examiners have had occasion to review these bullets both subjectively and objectively using striae counts. They have substantiated Biasotti's original premise that this correspondence is noted only in the groove impressions of a few lead bullets. Likewise, the land impressions of these lead bullets and the copper-jacketed test bullets have not shown the presence of any subclass characteristics. Nor have the groove impressions of the copper-jacketed bullets illustrated a degree of subclass characteristic correspondence that could be mistaken for an identification such as shown by the lead bullets. Unfortunately, due to the multiple handling of these bullets, the subclass characteristics of the lead bullets are currently not in the pristine shape they were in 1991.

¹ Bullets were test fired in 1979 by two student aids, now criminalists, Mike Guisto (BFS Stockton) and Robert Thompson (BATF Walnut Creek)

² R. Jinks of Smith & Wesson - personal correspondence to Criminalist T. Johnson, August 6, 1980.

³ AFTE Glossary Revision June 6, 1994.

⁴ Biasotti, A. A. "Rifling Methods - A Review and Assessment of the Individual Characteristics Produced AFTE Journal, Vol. 13 No. 3 July 1981.

⁵ PLASTISOL - A thermosetting plastic.

⁶ Lomoro, V. J. "32 SWL Caliber, F.I.E. Corp., Titanic revolvers AFTE Newsletter # 20 June 1972, AFTE Journal Vol. 6 No. 2, April 1974 and AFTE Journal Vol. 9 No. 2 July 1977.

⁷ Biasotti, A. "Letter to CCI E201 Criteria for identification course students" June 21, 1991.

⁸ Biasotti, A. (6) Ibid.

⁹ Biasotti, A and Murdock, J "Firearms and Toolmark Identification", Vol. 2 in MODERN SCIENTIFIC EVIDENCE AND: THE LAW AND SCIENCE OF EXPERT TESTIMONY (David L. Faigman, David H. Kaye, Michael J. Saks & Joseph Sanders eds.,